

| Brand Name | Viscosity | Nominal Phosphorus Level, PPM | Nominal Zinc Level, PPM | Product Description | Recommended Consumer Applications | API, ILSAC, and Other Industry Approvals*** | ACEA Approvals | GM Service Fill Approval | Ford Service Fill Approval | Chrysler Service Fill Approval | Mercedes- Benz Approval | BMW Approval | VW Approval | Porsche Approval |
|---|-----------|-------------------------------------|-------------------------------|---|--|--|-------------------|-----------------------------|----------------------------------|--------------------------------------|-------------------------------|-----------------|----------------|---------------------|
| Mobil 1™ Extended Performance | 0W-20 | 760 | 830 | Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect for 20,000 miles between oil changes – guaranteed. | Most vehicles that specify 0W-20 (newer Toyotas, Hondas, & GMs), 5W-20 and certain hybrids. | GF-6A, API SP, SP Resource Conserving, SN Plus, SN | | dexos1gen3 | WSS-M2C947-A,B1 WSS-M2C962-A1 | MS-6395 | | | | |
| Mobil 1™ Extended Performance | 5W-20 | 760 | 830 | Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect for 20,000 miles between oil changes – guaranteed. | Most vehicles that require 5W-20. | GF-6A, API SP, SP Resource Conserving, SN Plus, SN | | | WSS-M2C945-A,B1 WSS-M2C60-A1 | MS-6395 | | | | |
| Mobil 1™ Extended Performance | 5W-30 | 760 | 830 | Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect for 20,000 miles between oil changes – guaranteed. | Most vehicles that require 5W-30 or 10W-30. | GF-6A, API SP, SP Resource Conserving, SN Plus, SN, Honda/Acura HTO-06 | | dexos1gen3 | WSS-M2C946-A,B1 WSS-M2C961-A1 | MS-6395 MS-13340 | | | | |
| Mobil 1™ Extended Performance | 10W-30 | 760 | 830 | Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect for 20,000 miles between oil changes – guaranteed. | Most vehicles that require 10W-30. | GF-6A, API SP, SP Resource Conserving, SN Plus, SN | | | | | | | | |
| Mobil 1™ Extended Performance High Mileage | 0W-20 | 800 | 870 | Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect vehicles with over 75,000 miles for 20,000 miles between oil changes – guaranteed. | Most vehicles that specify 0W-20 (newer Toyotas, Hondas, & GMs), 5W-20 and certain hybrids. | GF-6A, API SP, SP Resource Conserving, SN Plus, SN | | | WSS-M2C947-A,B1 WSS-M2C962-A1 | MS-6395 | | | | |
| Mobil 1™ Extended Performance High Mileage | 5W-20 | 800 | 870 | Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect vehicles with over 75,000 miles for 20,000 miles between oil changes – guaranteed. | Most vehicles that require 5W-20. | GF-6A, API SP, SP Resource Conserving, SN Plus, SN | | | WSS-M2C945-A,B1 WSS-M2C960-A1 | MS-6395 | | | | |



| | | Nominal Phosphorus | Nominal Zinc Level, | | Recommended Consumer | API, ILSAC, and Other Industry | ACEA | GM Service | Ford Service Fill | Chrysler Service Fill | Mercedes- Benz | BMW | vw | Porsche |
|---|-----------|-----------------------|------------------------|--|--|---|-----------|---------------|----------------------------------|--------------------------|--------------------------------|----------|--------------------|----------------|
| Brand Name | Viscosity | Level, PPM | PPM | Product Description | Applications | Approvals*** | Approvals | Fill Approval | Approval | Approval | Approval | Approval | Approval | Approval |
| Mobil 1™ Extended Performance High Mileage | 5W-30 | 800 | 870 | Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect vehicles with over 75,000 miles for 20,000 miles between oil changes – guaranteed. | Most vehicles that require 5W-30 or 10W-30. | GF-6A, API SP, SP Resource Conserving, SN Plus, SN | | | WSS-M2C946-A,B1 WSS-M2C961-A1 | MS-6395 MS-13340 | | | | |
| Mobil 1™ ESP X3 | 0W-40 | 900 | 990 | Advanced full synthetic formula designed to help maintain the efficiency of emission systems in new emerging diesel and gasoline powered European vehicles | High power European engines requiring high HT/HS and GPF compatibility | API SN Plus | C3 | dexos2 | | | 229.31 / 229.51 / 229.52 | | 511 00 | Porsche C40 |
| Mobil 1™ ESP X2 | 0W-20 | 880 | 950 | Advanced full synthetic formula designed to help maintain the efficiency of emission systems in new emerging diesel and gasoline powered European vehicles | Most vehicles that require 0W-20. | API SP ETR | C5 / C6 | dexosD | | | 229.71 | | 508 00 / 509 00 | Porsche C20 |
| Mobil 1™ ESP | 0W-30 | 800 | 900 | Advanced full synthetic formula designed specifically for passenger car diesels that have particulate filters. | Low SAPS. Available at most MB dealers. | API SP ETR | С3 | | | | 229.31 / 229.51 / 229.52 | | 504 00 / 507 00 | Porsche C30 |
| Mobil™ 1 Supercar | 0W-40 | 900 | 990 | Advanced full synthetic formula designed for high performance cars to deliver outstanding overall performance | Corvettes and Camaros that call for 0W-40 oil. | | | dexosR | | | | | | |
| Mobil™ 1 Supercar | 5W-50 | 1100 | 1200 | Advanced full synthetic formula designed for high performance cars to deliver outstanding overall performance | Newer Corvettes that call for 5W- 50 oil. | API SP | | dexosR | | | | | | |
| Mobil 1™ ESP | 5W-30 | 800 | 900 | Advanced full synthetic formula designed specifically for passenger car diesels that have particulate filters. | Low SAPS. | API SP, Fiat S3 | C3 | | | | 229.51/ 229.52 | LL-04 | 504 00 / 507 00 | Porsche C30 |



| Brand Name | Viscosity | Nominal Phosphorus Level, PPM | Nominal Zinc Level, PPM | Product Description | Recommended Consumer Applications | API, ILSAC, and Other Industry Approvals*** | ACEA Approvals | GM Service Fill Approval | Ford Service Fill Approval | Chrysler Service Fill Approval | Mercedes- Benz Approval | BMW Approval | VW Approval | Porsche Approval |
|-------------------|--------------------------------------|-------------------------------------|-------------------------------|--|--|--|-------------------|-----------------------------|----------------------------------|--------------------------------------|-------------------------------|-----------------|--------------------|---------------------|
| Mobil 1™ FS | 0W-40 | 930 | 1000 | Advanced full synthetic formulation designed to meet the requirements of many European vehicles. | Many European vehicles. For high HT/HS applications. High SAPS | API SP, SN Plus, SN | A3/B4 | | | | 229.3 / 229.5 | LL-01 | 502 00 / 505 00 | Porsche A40 |
| Mobil 1™ FS X2 | 5W-50 | 930 | 1000 | Higher viscosity, advanced full synthetic formula designed for performance vehicles. | Many European vehicles. For high HT/HS applications. High SAPS | API SP, SN Plus, SN | A3/B4 | | | | 229.3 | | | Porsche A40 |
| Mobil 1™ FS | 5W-40 | 930 | 1000 | Advanced full synthetic formulation designed to meet the requirements of many European vehicles. | Many European vehicles. For high HT/HS applications. High SAPS | API SP, SN Plus, SN | A3/B4 | | | | 229.3 / 229.5 | LL-01 | 502 00 / 505 00 | Porsche A40 |
| Mobil 1™ | 0W-16 Advanced Fuel Economy | 760 | 830 | Advanced ultra-low viscosity full synthetic motor oil, engineered to enhance fuel economy and protect for 10,000 miles between oil changes – guaranteed. | Certain Toyota and Honda engines requiring 0W-16 oil. | GF-6B, API SP, SP Resource Conserving, SN Plus, SN | | | | | | | | |
| Mobil 1™ | 0W-20 Advanced Fuel Economy | 760 | 830 | Advanced full synthetic motor oil, engineered to enhance fuel economy and protect for 10,000 miles between oil changes – guaranteed. | Most vehicles that specify 0W-20 (newer Toyotas, Hondas, & GMs), 5W-20 and certain hybrids. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN | | dexos1gen3 | WSS-M2C947-A,B1 WSS-M2C962-A1 | MS-6395 | | | | |
| Mobil 1™ | 0W-30 Advanced Fuel Economy | 760 | 830 | Advanced full synthetic motor oil, engineered to enhance fuel economy and protect for 10,000 miles between oil changes – guaranteed. | Most vehicles that specify 5W-30 or 10W-30. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN | | dexos1gen3 | WSS-M2C953-A,B1 WSS-M2C963-A1 | | | | | |
| Mobil 1™ | 5W-20 | 760 | 830 | Advanced full synthetic motor oil, formulated to keep your engine running like new and protect for 10,000 miles between oil changes – guaranteed. | Most vehicles that require 5W-20. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN | | | WSS-M2C945-A,B1 WSS-M2C960-A1 | MS-6395 | | | | |



| Brand Name | Viscosity | Nominal Phosphorus Level, PPM | Nominal Zinc Level, PPM | Product Description | Recommended Consumer Applications | API, ILSAC, and Other Industry Approvals*** | ACEA Approvals | GM Service Fill Approval | Ford Service Fill Approval | Chrysler Service Fill Approval | Mercedes- Benz Approval | BMW Approval | VW Approval | Porsche Approval |
|--------------------------|-----------|-------------------------------------|-------------------------------|--|--|---|-------------------|-----------------------------|----------------------------------|--------------------------------------|-------------------------------|-----------------|----------------|---------------------|
| Mobil 1™ | 5W-30 | 760 | 830 | Advanced full synthetic motor oil, formulated to keep your engine running like new and protect for 10,000 miles between oil changes – guaranteed. | Most vehicles that require 5W-30. Corvette approved. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN, Honda/ Acura HTO-06 | | dexos1gen3 | WSS-M2C946-A,B1 WSS-M2C961-A1 | MS-6395 MS-13340 | | | | |
| Mobil 1™ | 10W-30 | 760 | 830 | Advanced full synthetic motor oil, formulated to keep your engine running like new and protect for 10,000 miles between oil changes – guaranteed. | Most vehicles that require 10W-30. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN | | | | | | | | |
| Mobil 1™ | 15W-50 | 1200 | 1320 | Advanced full synthetic motor oil, formulated to keep your engine running like new and protect for 10,000 miles between oil changes – guaranteed. | For high HT/ HS applications. Racing and Flat tappet applications. | API SN | A3/B3 | | | | | | | |
| Mobil 1™ High Mileage | 0W-20 | 800 | 870 | Advanced full synthetic motor oil, formulated to prevent leaks and protect engines with over 75,000 miles for 10,000 miles between oil changes – guaranteed. | Most vehicles that specify 0W-20 (newer Toyotas, Hondas, & GMs), 5W-20 and certain hybrids. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN | | | WSS-M2C947-A,B1 WSS-M2C962-A1 | MS-6395 | | | | |
| Mobil 1™ High Mileage | 5W-20 | 800 | 870 | Advanced full synthetic motor oil, formulated to prevent leaks and protect engines with over 75,000 miles for 10,000 miles between oil changes – guaranteed. | Most vehicles that require 5W-20. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN | | | WSS-M2C945-A,B1 WSS-M2C960-A1 | MS-6395 | | | | |
| Mobil 1™ High Mileage | 5W-30 | 800 | 870 | Advanced full synthetic motor oil, formulated to prevent leaks and protect engines with over 75,000 miles for 10,000 miles between oil changes – guaranteed. | Most vehicles that require 5W-30 or 10W-30. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN | | | WSS-M2C946-A,B1 WSS-M2C961-A1 | MS-6395 MS-13340 | | | | |
| Mobil 1™ High Mileage | 10W-30 | 800 | 870 | Advanced full synthetic motor oil, formulated to prevent leaks and protect engines with over 75,000 miles for 10,000 miles between oil changes – guaranteed. | Most vehicles that require 10W-30. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN | | | | | | | | |



| Brand Name | Viscosity | Nominal Phosphorus Level, PPM | Nominal Zinc Level, PPM | Product Description | Recommended Consumer Applications | API, ILSAC, and Other Industry Approvals*** | ACEA Approvals | GM Service Fill Approval | Ford Service Fill Approval | Chrysler Service Fill Approval | Mercedes- Benz Approval | BMW Approval | VW Approval | Porsche Approval |
|-----------------------------------|-----------|-------------------------------------|-------------------------------|--|--|---|-------------------|-----------------------------|----------------------------------|--------------------------------------|-------------------------------|-----------------|----------------|---------------------|
| Mobil 1™ High Mileage | 10W-40 | 800 | 870 | Advanced full synthetic motor oil, formulated to prevent leaks and protect engines with over 75,000 miles for 10,000 miles between oil changes – guaranteed. | Most vehicles that require 10W-40. | API SP, SN Plus, SN | | | | | | | | |
| Mobil 1™ Truck & SUV | 0W-20 | 760 | 830 | Advanced full synthetic motor oil, designed to protect during tough conditions like towing and hauling for 10,000 miles between oil changes – guaranteed. | Gasoline- powered truck and SUV engines. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN | | dexos1gen3 | WSS-M2C947-A,B1 WSS-M2C962-A1 | MS-6395 | | | | |
| Mobil 1™ Truck & SUV | 5W-20 | 760 | 830 | Advanced full synthetic motor oil, designed to protect during tough conditions like towing and hauling for 10,000 miles between oil changes – guaranteed. | Gasoline- powered truck and SUV engines. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN | | | WSS-M2C945-A,B1 WSS-M2C960-A1 | MS-6395 | | | | |
| Mobil 1™ Truck & SUV | 5W-30 | 760 | 830 | Advanced full synthetic motor oil, designed to protect during tough conditions like towing and hauling for 10,000 miles between oil changes – guaranteed. | Gasoline- powered truck and SUV engines. | GF-6A, API SP Resource Conserving, SP, SN Plus, SN | | dexos1gen3 | WSS-M2C946-A,B1 WSS-M2C961-A1 | MS-6395 MS-13340 | | | | |
| Mobil 1™ Turbo Diesel Truck | 5W-40 | 1100 | 1300 | Advanced full synthetic formula designed for modern diesel engines | Most diesel applications including low- emission engine designs. | API CK-4, CJ-4, CI-4 Plus, CI-4 API SN, Caterpillar ECF-2, ECF-3 | E7, E9 | | | | | | | |
| Mobil 1 Racing™ 4T | 10W-40 | 1150 | 1260 | Advanced full synthetic formula designed specifically for motorcycles where clutch lubrication is also important. | Most motorcycles where 10W-40 is specified. | API SN JASO MA/MA2 | | | | | | | | |
| Mobil 1™ V-Twin | 20W-50 | 1560 | 1770 | Advanced full synthetic formula designed specifically for motorcycles where clutch lubrication is also important. | Most motorcycles where 20W-50 is specified, especially V-Twin engines. | API SJ | | | | | | | | |



| Brand Name | Viscosity | Nominal Phosphorus Level, PPM | Nominal Zinc Level, PPM | Product Description | Recommended Consumer Applications | API, ILSAC, and Other Industry Approvals*** | ACEA Approvals | GM Service Fill Approval | Ford Service Fill Approval | Chrysler Service Fill Approval | Mercedes- Benz Approval | BMW Approval | VW Approval | Porsche Approval |
|--------------------|-----------|-------------------------------------|-------------------------------|--|---|---|-------------------|-----------------------------|-------------------------------|--------------------------------------|-------------------------------|-----------------|----------------|---------------------|
| Mobil 1 Racing™ | 0W-30 | 1770 | 1940 | Advanced full synthetic formula specifically designed to maximize horsepower under race conditions. | Race engines. Not recommended for street use. | | | | | | | | | |
| Mobil 1 Racing™ | 0W-50 | 1770 | 1940 | Advanced full synthetic formula specifically designed to maximize engine protection under race conditions. | Race engines. Not recommended for street use. | | | | | | | | | |

^{***}For a full list of industry and original equipment manufacturer approvals by product and viscosity, see the Product Data Sheets available online at mobiloil.com